

## Terracotta TOPCon N-type

# > 360 - 375 W

+19.2%

**Module efficiency**  
Module efficiency up to 19.2 %



**Colour RAL 8001**  
Perfect integration on demanding BIPV projects



**PID resistance**  
Certified according to IEC TS 62804 standards




**Increased resistance**  
Certified resistance against salt mist and ammonia



**Hail resistance**  
RG3/HW3 certified



**Easy to handle**  
Comfortable installation thanks to an optimized area size



**20** Years

**Product Warranty**  
+5 years for Premium Partners

**30** Years

**Performance Warranty**  
Linear Warranty

**2%** First year degradation

**0.55%** Annual degradation

**82.05%** Power in year 30

### Light up your world with Eurener

Eurener's extensive portfolio of certifications and awards is testament to our unwavering commitment to our partners and our deep sense of social and ethical responsibility.



Spanish Quality Worldwide





Awarded as TOP Brand PV



EcoVadis Platinum Medal for three consecutive years



# Eurener MEPV — TERRACOTTA 360-375W



Mechanical Specification	
Solar cells	N-Type monocrystalline silicon cells
Front Glass	3.2 mm thick tempered glass with high strength and ARC
Frame	Terracotta anodized aluminium
Junction Box	IP68, 3 by-pass diodes
Connector	Original MC4-Evo 2
Cable	1000 mm (±20%) length and 4 mm <sup>2</sup> section
Dimension	1722 x 1134 x 30 mm (±1%)
Area	1.95 m <sup>2</sup>
Weight	20.5 kg
Packaging	936 pcs/truck

Temperature Coefficients	
Temperature coefficient of Isc (α)	0.05 %/°C
Temperature coefficient of Voc (β)	-0.28 %/°C
Temperature coefficient of Pmax (γ)	-0.29 %/°C
Temperature range	-40 °C ~ +85 °C
Nominal operating cell temperature (NOCT)	45 ± 2 °C

	MEPV 360	MEPV 365	MEPV 370	MEPV 375
<b>Electrical Characteristics</b>				
<b>STC</b>				
Nominal power. Pmax	360 Wp	365 Wp	370 Wp	375 Wp
Short-circuit current (Isc)	11.61 A	11.69 A	11.78 A	11.87 A
Open-circuit voltage (Voc)	38.71 V	39.22 V	39.48 V	39.75 V
Maximum power current (Imp)	10.71 A	10.83 A	10.94 A	11.07 A
Maximum power voltage (Vmp)	33.63 V	33.69 V	33.83 V	33.98 V
Module efficiency	18.4 %	18.7 %	18.9 %	19.2 %
<b>Electrical Characteristics</b>				
<b>NOCT</b>				
Nominal power. Pmax	274 Wp	277 Wp	281 Wp	285 Wp
Short-circuit current (Isc)	9.17 A	9.19 A	9.26 A	9.33 A
Open-circuit voltage (Voc)	36.56 V	36.87 V	37.08 V	37.30 V
Maximum power current (Imp)	8.69 A	8.75 A	8.81 A	8.89 A
Maximum power voltage (Vmp)	31.49 V	31.69 V	31.88 V	32.08 V

\* STC: 1000 W/m<sup>2</sup>, module temperature 25°C, AM 1.5

\* NOCT: 800 W/m<sup>2</sup>, ambient temperature 20°C, AM 1.5

Operating parameters	
Maximum voltage	1500 V
Maximum series fuse rating. Ir	25 A
Power output tolerance	0 - +3 %
Voc and Isc tolerance	± 3 %
Fire rating	BROOF (t4) (EN 13501-5)
	Class A or C (UL 790)
Protection class	Class II (IEC 61140)
Mechanical loads	Front load 5400 Pa, Back load 2400 Pa

Corporate and product certificates
ECOVADIS rating - Platinum Medal (TOP 1%)
Solar Industry Forced Labor Prevention Pledge by SEIA
ISO9001:2015 - Quality Management Systems
ISO14001:2015 - Environmental Management System
WEEE compliance in Germany
PV CYCLE Italy
IEC 61215 - Terrestrial photovoltaic (PV) modules - Design qualification and type approval
IEC 61730 - Photovoltaic (PV) module safety qualification
IEC 61701 - Photovoltaic (PV) modules - Salt mist corrosion testing
IEC 62716 - Photovoltaic (PV) modules - Ammonia corrosion testing
IEC TS 62804 - Photovoltaic (PV) modules - Test methods for the detection of potential-induced degradation
Hail resistance HW3/RG3
Certificate of Factory Production Control (UK) - MCS
Fire reaction class: 1 - LAPI
Swissolar Quality Certificate



NOTE: All information contained in this data sheet is provided for general information purposes only. Product specifications may be subject to technical modifications. Reception, installation and use shall comply with the applicable Installation Manual, General Conditions of Sale and Warranty Terms and Conditions. The latest versions of all technical documentation are available at [www.eurener.com](http://www.eurener.com).

**SINCE**  
**1997**  
more than  
energy

**eurener.com**  
contact@eurenerworld.com  
+34 960 045 515  
Calle Colón, 1-23  
46004, Valencia. Spain

## European Experts in Residential modules

Since 1997 our main purpose has been to supply quality and long-lasting photovoltaic modules that allow us and future generations, to continue generating clean energy to take care of our planet.